



Illustrative photo

The iDialog Rack range is the ideal solution for the protection of peripherals in the home and in office environments.

iDialog is an easy-to-install, economic solution for anyone wishing to protect:

- IT equipment such as PCs, Media Centres and peripherals
- TVs, Home Cinema systems, Satellite and Digital Terrestrial Receivers and DVD recorders and players
- xDSL modems and routers
- Small home appliances
- VoIP and network applications

Features

- Maximum reliability in the protection of PCs thanks also to the monitoring and shutdown software PowerShield³
- Suitable for installation on PC's with Windows 8, 7, Hyber-V, 2012, 2008, Linux, Mac OSX operating system
- Small size: with its compact shape, iDialog Rack can be placed on any small rack
- Noise-free running, iDialog is also suitable for protecting your non-professional, digital equipment items such as Home Cinema, CD Writers, DVD, Satellite and Digital Terrestrial receivers

2 – year warranty



Technical specification

Models	IDR600	IDR1200
Power	600VA / 360W	1200VA / 720W
Input	IDR600	IDR1200
Nominal voltage	220 – 240 V _{AC}	
Input voltage tolerance	230 V _{AC} (+20/-25 %)	
Nominal frequency	50 / 60 Hz automatic selection	
Output	IDR600	IDR1200
Frequency during battery operation	50 or 60 Hz (± 1%)	
Wave form on battery	Pseudo sinewave	
Batteries	IDR600	IDR1200
Type	VRLA, AGM maintenance-free lead-acid	
Recharge time / back-up time	2 - 4 hours / back-up time ± 5 min (depends on load)	
Other features	IDR600	IDR1200
Net weight	5,5 kg	9 kg
Dimensions (w x d x h)	438 x 230 x 87 mm (19IN/2U)	438 x 300 x 87 mm (19IN/2U)
Protections	Excessive low battery - overvoltage - short circuit	
Communication	USB + RS232	
Safety compliance and EMC conformance	EN62040-1-1, Directive 73/23 EEC, Directive 93/68 EEC, EN 62040-2 cl. B, Directive 89/336 EEC, Directive 92/31 EEC	
Operating temperature	0°C – +40 °C	
Altitude and relative humidity	6000 m max. altitude; < 95% no condensing	
Accessories	Rack handles, User guide	
Available Options	NETMAN 204 + box, MULTICOM 302 + box	



Illustrative photo

A2B, s.r.o. reserves the right to change any specifications without prior notice (V092016)