



Illustrative photo

HIGHLIGHTS

- High UPS reliability
- Operating mode selection
- High quality output voltage
- Simplified installation
- High battery reliability
- Low impact on the mains

Sentinel Power is the ideal solution for powering sensitive, mission critical systems such as safety devices (electro-medical devices), ensuring maximum power reliability.

The series includes 5-6 kVA single/single-phase and 6.5-8-10 kVA single/single-phase and three/single-phase models with on-line double conversion technology (VFI): the load is powered continuously by the inverter which supplies a sinusoidal voltage, filtered and stabilised in terms of voltage, form and frequency. Input and output filters provide significant further immunity from mains disturbances and lightning strikes.

In terms of technology, performance (selectable Economy and Smart Active Modes) and diagnostics (LCD custom display, RS232 and USB interfaces with Powershield³ software included, ESD input, interface slot for optional boards),

Sentinel Power is one of the best UPS available on the market.

High UPS reliability

- Total microprocessor control.
- Interruption-free static and manual bypass.
- Specifications guaranteed up to 40 °C (the components are designed to work at high temperatures and thus are subject to less stress at normal temperatures).

Operating mode selection

The operating mode can be programmed via software or manually via the front display panel.

- **On line**
- **Economy Mode:** to increase efficiency (up to 98%), allows for the selection of Line Interactive technology (VI) to power low priority loads from the mains supply.
- **Smart Active:** the UPS automatically decides upon the operating mode (VI or VFI) based on the quality of the mains power supply.
- **Emergency:** the UPS can be selected to function only when the mains power supply fails (emergency only mode).
- **Frequency converter** operation (50 or 60 Hz).

High quality output voltage

- Even with non-linear loads (IT loads with a crest factor of up to 3:1).
- High short circuit current on bypass.
- High overload capacity: 150% by inverter (even with mains failure).
- Filtered, stabilised and reliable voltage (double conversion on-line technology - VFI compliant with EN 62040-3), with filters for the suppression of atmospheric disturbances.

- Power factor correction: UPS input power factor close to 1 and sinusoidal current uptake.

Simplified installation

- UPS can be installed on a single-phase or three-phase distribution network
- Output terminal board + 2 IEC sockets for powering local consumers (computers, modems, etc.)
- Simplified positioning (built-in castors).

High battery reliability

- Automatic and manual battery test
- Reduced ripple component (detrimental to the batteries) using a low ripple current discharge (LCRD) system
- Unlimited extendible runtime using matching Battery Boxes
- The batteries do not cut in during mains failures of <40 ms (high hold up time) or when the input supply is between 84 V to 276 V.

Energy-share

Two 10 A configurable IEC output sockets allow for runtime optimisation by programming the switching off of low priority loads on mains failure; alternatively, emergency loads that are normally not powered when mains is present can be activated.

Low impact on the mains

Sinusoidal uptake of input current on single-phase/single-phase series.

Other features

- Advanced diagnostics: status, measurements and alarms available on custom LCD display
- Low noise (<40 dBA): can be installed in any environment thanks to its high frequency switching

inverter and PWM load-dependent digitally controlled fan (>20 kHz, value above audible range)

- Auto restart (automatic when mains supply is restored, programmable via software or display panel)
- Emergency function: the UPS can be selected to function only when the mains power supply fails (emergency lights)
- Back-feed protection standard: to prevent energy from being fed back to the network
- UPS digital updating (flash upgradeable).

Advanced communications

Compatible with Riello UPS TeleNetGuard remote monitoring

Advanced multi-platform communications for all operating systems and network environments: PowerShield³ monitoring and shutdown software for Windows operating systems 8, 7, Hyper-V, 2012, 2008, and previous versions, Mac OS X, Linux, VMWare ESXi, Citrix XenServer and other Unix operating systems

- RS232 serial port
- Plug and play function
- Slot for installation of communications boards

OPTIONS

Software


PowerShield³
PowerNetGuard

Accessories

NETMAN 204
MULTICOM 302
MULTICOM 352
MULTICOM 372
MULTICOM 382
MULTICOM 401
MULTI I/O
Interface kit AS400
MULTIPANEL
RTG 100
Manual Bypass MBB 100 A

Product accessories

Isolation transformer module (hlp) mm/kg: 500 x 400 x 265 / 80 (only for 5000-6000 VA models)





UPS SENTINEL POWER 5-10 kVA



Technical specification

Models	SPW 5000	SPW 6000	SPT 6500	SPT 8000	SPT 10000
Power	5000 VA 4000 W	6000 VA 4800 W	6500 VA 5200 W	8000 VA 6400 W	10000 VA 8000 W
Input					
Nominal voltage	220 – 230 – 240V 1 ph		220 –230–240V 1 ph or 380-400-415Vac 3 ph + N		
Minimum voltage without battery intervention	170V at 100% load/ 140V at 50% load				
Nominal frequency	50 / 60 Hz± 5Hz				
Bypass					
Voltage tolerance	180 – 264 Vac (selectable in Economy Mode and Smart Active Mode)				
Frequency tolerance	Selectable frequency± 5%				
Overload Times	125% for 4 seconds, 150% for 0,5 seconds				
Batteries					
Type	VRLA AGM maintenance-free lead based				
Recharge time	6-8 hours				
Output					
Nominal voltage	220 - 230 - 240 Vac selectable				
Voltage distortion	< 3% with linear load / < 6% with non-linear load				
Frequency	50/60 Hz selectable or with automatic selection				
Static variation	± 1,5 %				
Dynamic variation	≤ 5% in 20 ms				
Waveform	Sinusoidal				
Crest factor	≥ 3 : 1				
Other features					
Weight (kg)	91	92	105	106	
Dimensions (wxdxh) (mm)	282 x 785 x 615				
Technology	On-line dual conversion				
Smart Active efficiency	Up to 98%				
Operating temperature	0°C / + 40 °C, optimal + 15°C + 25°C				
Relative humidity	< 95% non-condensing				
Protections	Overcurrent - short-circuit - overvoltage - undervoltage - temperature - excessive low battery				
Standards	EN62040-1, EMC EN 62040-2 a Directives 2006/95/EC; 2004/108/EC, EN 62040-3				
Communications	USB + RS232 + slot for communications interface				
Input plugs	Terminal board				
Output sockets	Terminal board + 2 IEC 320 C13				
Colour	Dark grey (RAL 7016)				
Noise level at 1 m	< 45 dBA				
Moving the UPS	castors				

A2B, s.r.o. reserves the right to change any specifications without prior notice (76-000242-01)